

## **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

1. (original) A method of manipulating a solid, which comprises:
  - (a) providing a bed of powder of known weight and uniform height;
  - (b) inserting a tube a controlled distance into the bed to obtain a plug of powder, wherein the tube has an interior that accommodates a means of ejecting materials from within the tube;
  - (c) removing the tube from the bed; and
  - (d) ejecting the plug of powder.
2. (original) The method of claim 1, wherein:
  - (a) the tube is inserted completely through the bed;
  - (b) the plug of powder is obtained by compression;
  - (c) the means of ejecting the plug is a piston, vibration, pressurized gas, or a liquid;
  - (d) the means of ejecting the plug of (c) is a piston;
  - (e) the method does not substantially affect the form of the solid; or
  - (f) the powder comprises an active pharmaceutical ingredient.
3. (original) A method for dispensing a controlled mass of a solid, which comprises:
  - (a) processing the solid into a powder with an average particle size of less than about 200 micrometers;
  - (b) forming a powder bed with a predetermined mass and uniform height from a portion of the powder;

- (c) inserting a tube a controlled distance into the powder bed to obtain a plug of powder, wherein the tube has an interior that accommodates a means for ejecting materials from within the tube;
- (d) lifting the tube from the powder bed;
- (e) moving the tube over a target location; and
- (f) ejecting a plug of powder onto target location.

4. (currently amended) The method of claim 3, wherein:

- (a) the method further comprises:
  - (i) providing a grille plate with an array of holes sized so that the tube can pass through each with a small clearance; and
  - (ii) holding the grille plate on top of the powder bed; the powder bed is prevented from breaking apart upon insertion of the tube;
- (be) a method to form the powder bed comprises:
  - (i) providing a source receptacle assembly comprising:
    - (1) a source receptacle with sides, a top surface, a bottom face, and at least one cylindrical hole that passes through and is perpendicular to the bottom face; and
    - (2) a base plate that is removeably attached to the bottom face;
  - (ii) dispensing a predetermined mass of the powder into the cylindrical hole;
  - (iii) providing a cylindrical pin with at least one flat, perpendicular end face;
  - (iv) inserting the cylindrical pin into the cylindrical hole and pressing the pin into the powder with a predetermined force;
  - (v) rotating the cylindrical pin through an angle of at least 1 degree of rotation with the predetermined force applied; and simultaneously rotating and lifting the pin out of the cylindrical hole;
- (gd) a method is used for forming the powder bed comprising the steps of:

- (i) providing a source receptacle assembly comprising:
  - (1) a source receptacle with sides, a top face, a bottom surface, and at least one cylindrical hole that passes through and is perpendicular to the top face;
  - (2) a close fitting cylinder disposed inside of the cylindrical hole; and
  - (3) a cylinder locking means which allows the close fitting cylinder to be either locked to or disengaged from the source receptacle;
- (ii) dispensing a predetermined mass of the powder into the cylindrical hole through the top face of the source receptacle;
- (iii) providing a slide plate with at least one flat face;
- (iv) pressing the flat face of the slide plate against the top face of the source receptacle;
- (v) disengaging the cylinder locking means;
- (vi) pressing the cylinder into the powder with a predetermined force;
- (vii) rotating the cylinder through an angle of at least 1 degree of rotation with the predetermined force applied;
- (viii) engaging the cylinder locking means; and
  - sliding the slide plate off of the top face of the source receptacle;
- (de) pressures applied to the powder are low enough so as to not substantially affect the form of the powder;
- (ef) the powder comprises an active pharmaceutical ingredient;
- (fg) the ejecting means is a close fitting pin disposed in the interior of the tube;
- (gh) the plug inside the tube is compressed prior to being ejected;
- (hi) the tube is inserted completely through the powder bed;
- (ij) the ejecting means is a close fitting pin with sides and a face disposed in the interior of the tube, and the close fitting pin is held stationary relative to the tube while the tube is inserted into the powder bed a predetermined depth sufficient to make the pin face contact the powder;

(jk) the tube is inserted into the powder with a predetermined force applied to it;

(kl) the tube is inserted into the powder bed a predetermined depth;

(lm) the tube is a hollow needle; or

(mn) a wide variety of solids can be dispensed in controlled amounts without substantially affecting their form.

5. (withdrawn) An apparatus for manipulating a solid, which comprises:

(a) a punching assembly comprising a tube having an interior, a piston located within the interior of the tube, a first actuator capable of adjusting the vertical position of the tube, and a second actuator capable of moving the piston within the tube;

(b) a powder bed assembly mounted below the punching assembly, comprising a source plate and a receiving plate; and

(c) a means of positioning the punching assembly over the source plate and the receiving plate.

6. (withdrawn) An apparatus for dispensing powder which comprises:

(a) a punching assembly comprising a tube having an interior, close fitting pin disposed inside the interior of the tube, a first actuator capable of adjusting the vertical position of the tube, a second actuator capable of moving the pin within the tube;

(b) a source station comprising at least one powder bed of predetermined mass and uniform height, and a structure to support the powder bed;

(c) a receiving plate mounted below the punching assembly; and

(d) a means for positioning the punching assembly over the source plate and the receiving plate.

7. (withdrawn) The apparatus of claim 6, wherein:

(a) the first actuator and the second actuator are pneumatically driven linear actuators;

- (b) the first actuator and the second actuator are electronically driven linear servos;
  - (c) the means for positioning the punching assembly comprises perpendicularly mounted electronically driven linear servos;
  - (d) a wash station is included which contains means for washing away powder from the tube and the pin, and drying the hollow needle and the pin;
  - (e) a weigh station is included which contains means for weighing powder that is dispensed into it;
  - (f) the tube is a hollow needle; or
  - (g) a wide variety of solids can be dispensed in controlled amounts without substantially affecting their form.
8. (withdrawn) A method of manipulating a solid, which comprises:
- (a) blending a controlled amount of the solid with a liquid to provide a slurry;
  - (b) dispensing a controlled amount of the slurry; and
  - (c) removing the liquid to provide an amount of the solid, wherein the amount of the solid is less than about 1 mg.
9. (withdrawn) The method of claim 8, wherein:
- (a) the amount of solid is less than about 0.5 mg;
  - (b) the amount of solid is less than about 100 micrograms;
  - (c) the means of removing the liquid is evaporation, filtration, or sedimentation;
  - (d) the solid comprises an active pharmaceutical ingredient;
  - (d) the solid comprises an active pharmaceutical ingredient;
  - (e) the method does not substantially affect the form of the solid;
  - (f) the liquid comprises a wetting agent and water;
  - (g) the wetting agent is isopropyl alcohol, methanol, PVP, Tween®, or sodium lauryl sulfate; or
  - (h) solid state analysis is performed after removing the liquid to verify that the solid has not changed form.

10. (withdrawn) A method of manipulating a solid, which comprises:  
contacting particles of the solid with a surface comprising a plurality of discrete adhesive areas separated by non-adhesive areas, wherein the size of the adhesive areas is smaller than about  $5\text{ cm}^2$ , under conditions sufficient to adhere the particles non-electrostatically to an adhesive area; and  
adhering the particles non-electrostatically to the adhesive area.
11. (withdrawn-currently amended) The method of claim 10, wherein:  
less than about 1 mg of solid is adhered to an adhesive area;  
less than about 0.5 mg of solid is adhered to an adhesive area;  
(~~ae~~) less than about 0.25 mg of solid is adhered to an adhesive area;  
(~~bd~~) the adhesive material is a pressure sensitive adhesive, a silicone, or a hydrogel;  
(~~ce~~) the solid comprises an active pharmaceutical ingredient; or  
(~~df~~) the method does not substantially affect the form of the solid.
12. (withdrawn) An apparatus for manipulating a solid, which comprises:  
(a) a surface, comprising a plurality of discrete adhesive areas separated by non-adhesive areas, wherein the size of the adhesive areas is smaller than about  $5\text{ cm}^2$ , under conditions sufficient to adhere the particles non-electrostatically to an adhesive area at least a portion of which is coated with an adhesive;  
(b) a container capable of holding powder; and  
(c) a means of contacting the adhesive portion of the surface with powder in the container.
13. (withdrawn) The apparatus of claim 12, wherein the adhesive material is a pressure sensitive adhesive, a silicone, or a hydrogel.
14. (withdrawn) A method for manipulating a solid, which comprises:

dispensing a known amount of solid into a source chamber;  
compressing the solid;  
moving a slide plate such that a dose chamber traverses the solid;  
moving the dose chamber over a target well; and  
ejecting a plug of solid.

15. (withdrawn) The method for manipulating a solid of claim 14, wherein
- (a) the slide plate in step (c) is moved in a criss-cross or in a spiral trajectory;
- or
- (b) the source chamber is subjected to vibration or mixing in step (c).

16. (withdrawn) An apparatus for manipulating a solid, which comprises:
- a slide plate comprising a dose chamber;
  - a powder bed assembly mounted below the slide plate, comprising a source chamber and a receiving plate; and
  - a means for positioning the slide plate over the source plate and the receiving plate.

17. (withdrawn) The apparatus for manipulating a solid of claim 16, wherein:
- the apparatus further comprises a microbalance; or
  - the slide plate comprises a dose chamber in the form of a grid cutter.

18. (withdrawn) A method of manipulating a solid, which comprises:
- dispensing a known amount of solid into a source chamber;
  - compressing the solid;
  - moving a slide plate directly below the source chamber;
  - pressing the solid through a grid cutter to make multiple plugs;
  - moving the slide plate to an ejector pin; and
  - propelling ejector pin down to eject a solid plug into a target well.

19. (withdrawn) The method of claim 18, wherein:

the height of each partition in the grid cutter is controlled by a micrometer;  
the target well is controlled by an x servo and a y servo; or  
the target well is controlled by an x linear actuator and a y linear actuator.

20. (withdrawn) A method of transferring a solid, which comprises:  
gripping a vessel containing a solid with a clamp;  
attaching a swing arm to the clamp;  
accelerating the swing arm through an arc trajectory until a hard stop is impacted;  
and  
placing a target well directly below the stopped position of the vessel.
21. (withdrawn) The method of claim 20, wherein:  
a carousel enables simultaneous transferring and weighing;  
the target well is controlled by an x servo and a y servo;  
the target well is controlled by an x linear actuator and a y linear actuator;  
solid transfer is promoted by a vibrating actuator; or  
premature solid transfer is prevented by a retractable shield.
22. (withdrawn) An apparatus for transferring a solid, which comprises:  
a vessel containing a solid gripped by a clamp;  
a swing arm attached to the clamp;  
a hard stop;  
a target well; and  
an x actuator and a y actuator to control the position of the target well.
23. (withdrawn) The apparatus of claim 22, wherein:  
the actuators are linear servos;  
the apparatus further comprises a carousel;  
the apparatus further comprises a vibrating actuator;  
the apparatus further comprises a retractable shield;  
the target vessel is a multi-well plate; or



the apparatus further comprises a microbalance.

24. (withdrawn)      A method of transferring a solid, which comprises:  
gripping a vessel with a mechanical device mounted to xy linear actuators; and  
moving the vessel between a receiving plate and a microbalance using the  
mechanical device mounted to the xy linear actuators.
25. (withdrawn)      An apparatus for transferring a solid, which comprises:  
a vessel gripped by a mechanical device;  
the mechanical device is mounted to xy linear actuators;  
a receiving plate; and  
a microbalance.
26. (withdrawn)      A method for mixing small amounts of solids, which comprises:  
placing the solid in a filter-bottom well;  
sealing the well; and  
injecting gas into the well.
27. (withdrawn)      The method of claim 26, wherein:  
the well is sealed with a filter plate;  
the well is sealed with a lid; or  
the seal is pierceable.
28. (withdrawn)      An apparatus for mixing small amounts of solids, which  
comprises:  
a well with a filter bottom containing solids;  
a seal; and  
a means for injecting gas into the well.
29. (withdrawn)      A method to weigh a small amount of solid, which comprises:  
supporting a low-mass container with a cradle;

positioning the cradle so the low-mass container is above a weigh platform;  
lowering the cradle so the low-mass container is supported by the weigh platform;  
and  
weighing the solid.

30. (withdrawn) An apparatus to weigh a small amount of solid, which comprises:  
a low mass container containing solid and supported by a cradle;  
a weigh platform; and  
means for lowering the cradle so the low-mass container is supported by the  
weigh platform.

31. (withdrawn) The apparatus of claim 30, further comprising:  
xy linear actuators; or  
a two-dimensional array of low-mass containers.

32. (withdrawn) A method for measuring the mass of a small amount of solid,  
which comprises:  
coring a plug of powder with a coring tube;  
generating a voltage signal;  
applying the voltage signal to a piezoelectric actuator affixed to the coring tube;  
and  
measuring the displacement of the coring tube with a laser.

33. (withdrawn) The method of claim 32, wherein:  
the voltage signal is a swept-sine signal; or  
the frequency of the applied voltage signal is between 6.3 kHz and 7.1 kHz.

34. (withdrawn) An apparatus for measuring the mass of a small amount of solid,  
which comprises:  
a coring tube;  
a function generator;

a piezoelectric actuator affixed to the coring tube,  
a laser aligned with the coring tube.

35. (withdrawn) A method for measuring the mass of a small amount of solid, which comprises:
- attracting dielectric particles to an electrode by imposing a non-uniform electric field;
  - generating a voltage signal;
  - applying the voltage signal to a piezoelectric actuator affixed to the electrode; and
  - measuring the displacement of the electrode with a laser.
36. (withdrawn) The method of claim 35, wherein:
- (a) the voltage signal is a swept-sine signal; or
  - (b) the frequency of the applied voltage signal is between 3.6 kHz and 4.0 kHz.
37. (withdrawn) An apparatus for measuring the mass of a small amount of solid, which comprises:
- an electrode;
  - a function generator;
  - a piezoelectric actuator affixed to the electrode; and
  - a laser aligned with the electrode.